3MP Outdoor Wi-Fi Bullet Camera C2-3WL

Introduction



C2-3WL is an outdoor dual-light camera developed by our company, with 3MP HD resolution, supporting BT5.0, Wi-Fi network connection, supporting human detection, regional vigilance, dual-light vigilance, and full-color night vision. It is suitable for family outdoor, villas, parks, scenic spots, parking lots and other monitoring places.

Main Features



Wi-Fi



Human Detection



Alarm Push



Two-way Talk



Dual Light Alert



Voice Alarm Bells



Full Color Night Vision



Area Vigilance



IP66





Cloud Storage



TF Card Storage

Dimension







Product Parameters

Model	C2-3WL
Camera	
Resolution	3MP
Image Sensor	1/2.9" Low illumination Sensor
Min. Illumination	Color: 0.1Lux @(F2.0,AGC ON); 0 Lux with IR
	B/W: 0.01 Lux @ (F2.0,AGC ON),0 Lux with IR
Lens	4(±0.3)mm@F2.0; Diagonal: 97.4°, Horizontal: 82.3°, Vertical: 44.7°
Shutter Speed	Self-adaptive shutter
Fill Light	4*850nm IR fill lights&4*white led fill lights
Night Vision	Full-color night vision/Infrared night vision/Dual-light alert
DNR	3D DNR
Audio Input	Built-in microphone
Audio Output	Built-in speaker
Video Storage	TF card storage/Cloud storage
Image	
Max. Resolution	2304*1296
Frame Rate	20FPS
Buttons & Interfaces	
Network Interface	1*RJ45 (10M / 100M Adaptive Ethernet Port)
Storage Interface	1*TF card storage interface (max. 256G)
Power Interface	1*DC 12V/1A power interface
Button	1*Reset button
Compression	
Video Compression	H.265/H.264
Audio Compression	G.711A
Network	
Protocol	JFTECH cloud proprietary protocol
Interface Protocol	JFTECH cloud proprietary protocol
General Function	Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark
Wireless Parameters	
Wi-Fi Standard	IEEE 802.11b/g/n
Frequency Range	2.4 GHz ~ 2.4835 GHz
General	
Operating Conditions	-10°C ~ 50°C, Humidity 95% or less (non-condensing)
Power Supply	DC 12V/1A
Night Vision Distance	30m
Pickup Distance	5m
Housing Material	ABS, PC, Metals
Net Weight	About 213g
Dimensions	About 63mm*80mm*155mm
IP Grade	IP66

