

# 2K<sup>+</sup> Outdoor 4G AOV PT Camera

S2-4GS

## Introduction



The S2-4GS is an outdoor AOV 4G PT camera developed by Jaify capable of continuous 24/7 recording. It features a removable SIM card slot for 4G network connectivity and is powered by a built-in rechargeable lithium battery, which also supports solar panel charging for extended operation. With 2K<sup>+</sup> (4MP) HD imaging and 360° panoramic monitoring, it offers human detection, human tracking, and Ultra full-color night vision. IP66-rated waterproof and dustproof for outdoor use. It is suitable for monitoring applications in areas without network or power infrastructure, such as residential outdoor spaces, scenic areas, orchards, farmlands, and fish ponds.

## Main Features



4G Connected



Human Detection



Human Tracking



360° Panorama



All-day Recording



Voice Alarm Bells



Ultra Full Color Night Vision



Built-in Battery



TF Card Storage




Cloud Storage



IP66

## Dimension



## Product Parameters

Camera	
<b>Model</b>	S2-4GS
<b>Resolution</b>	2K*(4MP)
<b>Image Sensor</b>	1/2.9" High-performance CMOS sensor
<b>Min. Illumination</b>	Color: 0.001Lux @ (F1.0, AGC ON); 0 Lux with light
<b>Lens</b>	4mm @F1.0
<b>Field Of View</b>	Diagonal: 95.5°, horizontal: 81.3°, vertical: 44.3°
<b>Shutter Speed</b>	Self-adaptive shutter
<b>Fill Light</b>	9*white led fill lights
<b>Night Vision</b>	Ultra Full-color night vision
<b>DNR</b>	3D DNR
<b>Audio Input</b>	Built-in microphone
<b>Audio Output</b>	Built-in speaker
<b>PT Angle</b>	Horizontal 355°, vertical 95°
<b>Video Storage</b>	TF card storage/Cloud storage
Image	
<b>Max. Resolution</b>	2560*1440
<b>Frame Rate</b>	12FPS
Buttons & Interfaces	
<b>Storage Interface</b>	1*TF card storage interface (max. 512G)
<b>Power Interface</b>	1*Type-C power interface
<b>SIM Card Interface</b>	1*Self-popping SIM card slot
<b>Button</b>	1*Reset button, 1*Power switch button
Compression	
<b>Video Compression</b>	H.265/H.264
<b>Audio Compression</b>	G.711A
Network	
<b>One-touch Provisioning</b>	4G network provisioning
<b>Protocol</b>	JFTECH cloud proprietary protocol
<b>Interface Protocol</b>	JFTECH cloud proprietary protocol
<b>General Function</b>	Anti-Flicker, Dual-Stream, Password Protection, Watermark
Wireless Parameters	
<b>4G Frequency Band</b>	EU Version: LTE FDD: B1/B3/B5/B7/B8/B20/B28 APAC Version: LTE FDD: B1/B3/B5/B8 LTE TDD: B34/B38/B39/B40/B41
General	
<b>Operating Conditions</b>	-10°C ~ 50°C, Humidity 95% or less (non-condensing)
<b>Power Supply</b>	Built-in 10400mAh lithium battery &7W solar panel
<b>Night Vision Distance</b>	30m
<b>Pickup Distance</b>	5m
<b>Housing Material</b>	ABS, PC
<b>Net Weight</b>	About 914g
<b>Dimensions</b>	About 153mm*185mm*293mm
<b>IP Grade</b>	IP66