

3K⁺ Outdoor Wi-Fi Dual-lens PT Camera

S2-6WL-D2

Introduction



S2-6WL-D2 is an outdoor Wi-Fi dual-lens PT camera developed by Jaify, with dual-lens design, which can monitor two different areas at the same time, with 3K⁺ (6MP) resolution. Supports BT5.0 pairing and Wi-Fi connectivity, and is also compatible with wired Ethernet connections. Supporting human detection, human tracking, regional vigilance, dual-light alert, and full-color night vision. IP66-rated waterproof and dustproof for outdoor use. It is suitable for family outdoor, villas, parks, scenic spots, parking lots.

Main Features



Wi-Fi Connected



Human Detection



Human Tracking



360° Panorama



Two-Way Talk



Voice Alarm Bells



Full Color Night Vision



Dual-Light Alert



TF Card Storage



Cloud Storage




IP66



Two-way Monitoring

Dimension



Product Parameters

| Camera | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Model | S2-6WL-D2 |
| Resolution | 3K+(6MP) |
| Image Sensor | 2*1/2.9" High-performance CMOS sensor |
| Min. Illumination | Color: 0.05Lux @ (F1.6, AGC ON), 0 Lux with light B/W: 0.05 Lux @ (F1.6, AGC ON), 0 Lux with IR |
| Lens | 4mm @F1.6+6mm @F1.6 |
| Field Of View | Fixed Lens: Diagonal: 95°, Horizontal: 79°, Vertical: 42° PT Lens: Diagonal: 60.5°, Horizontal: 50.5°, Vertical: 29° |
| Shutter Speed | Self-adaptive shutter |
| Fill Light | 9*850nm IR fill lights&17*white led fill lights |
| Night Vision | Full-color night vision/Infrared night vision/Dual-light alert |
| DNR | 3D DNR |
| Audio Input | Built-in microphone |
| Audio Output | Built-in speaker |
| PT Angle | Horizontal 355°, vertical 95° |
| Video Storage | TF card storage/Cloud storage |
| Image | |
| Max. Resolution | 2304*2592 |
| Frame Rate | 12FPS |
| Buttons & Interfaces | |
| Storage Interface | 1*TF card storage interface (max. 256G) |
| Power Interface | 1*DC 12V/1A Power interface |
| Wired Network | 1*RJ45 (10M / 100M Adaptive Ethernet Port) |
| Button | 1*Reset button |
| Compression | |
| Video Compression | H.265/H.264 |
| Audio Compression | G.711A |
| Network | |
| One-touch Provisioning | Wi-Fi network provisioning |
| Protocol | JFTECH cloud proprietary protocol |
| Interface Protocol | JFTECH cloud proprietary protocol |
| General Function | Anti-Flicker, Dual-Stream, Mirroring, Password Protection, Watermark |
| Wireless Parameters | |
| Wi-Fi Standard | IEEE 802.11b/g/n |
| Frequency Range | 2.4 GHz ~ 2.4835 GHz |
| General | |
| Operating Conditions | -10°C ~ 50°C, Humidity 95% or less (non-condensing) |
| Power Supply | DC 12V/1A |
| Night Vision Distance | 30m |
| Pickup Distance | 5m |
| Housing Material | ABS, PC |
| Net Weight | About 788g |
| Dimensions | About 153mm*208mm*292mm |
| IP Grade | IP66 |

